

CE SCHOOL BUS

Sales Proposal For:

Hot Springs Public Schoo

Presented By:

HARLOW'S BUS SALES,INC

Code Description

PB11000 Base Chassis, Model CE SCHOOL BUS with 276.00 Wheelbase, N/A CA, and 176.00 Axle to Frame.

1570 TOW HOOK, FRONT (2) Frame Mounted

1ANA AXLE CONFIGURATION {Navistar} 4x2

1CAC FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x

77.8mm x 8.0mm); 489.2" (12425mm) Maximum OAL

1LNT CROSSING GATE, FRONT Omit Item

1LSG BUMPER, FRONT Contoured, Steel, Painted Gloss Black, Severe Duty

Notes

: Bumper Thickness is .25"

1SAL CROSSMEMBER, REAR, AF (1)

1WJE WHEELBASE RANGE 276" (700cm) Only

1WRP TOW HOOK, REAR (2) Mounted on Lower Rail Flange

2ASH AXLE. FRONT NON-DRIVING {Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity

3ADB SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 10,000-lb Capacity, with Shock

Absorbers

Includes

: SPRING PINS Rubber Bushings, Maintenance-Free

4091 BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE LINES Color and Size Coded Nylon

: DRAIN VALVE Twist-Type

: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6

4AZS AIR BRAKE ABS (Bendix AntiLock Brake System) 4-Channel (4 Sensor/4 Modulator) Electronic Stability

Program, with Automatic Traction Control

4EDN AIR DRYER (Bendix AD-9SI) with Heater, Includes Safety Valve

4EXP BRAKE CHAMBERS, FRONT AXLE (Bendix) 20 Sqln

4EXU BRAKE CHAMBERS, REAR AXLE (Bendix EverSure) 30/30 Sqln Spring Brake

4EYD AIR DRYER SHIELD to Protect from Debris

4GBM BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake

4LAG SLACK ADJUSTERS, FRONT {Gunite} Automatic
4LGG SLACK ADJUSTERS, REAR {Gunite} Automatic
4SPA AIR COMPRESSOR {Cummins} 18.7 CFM

4VLE AIR DRYER LOCATION Mounted Inside Engine Compartment, Right Side
4VLY AIR TANK LOCATION (1) Mounted Inside & Below Left Rail, Back of Cab

4WZT GVWR LIMITATION FOR BUS with Air Brakes, Limited to 33,000-lbs Maximum to meet FMVSS 121

Requirements, for Conventional Bus

4XDP BRAKES, FRONT (Meritor 16.5X5 Q-PLUS CAST) Air S-Cam Type, Cast Spider, Fabricated Shoe, Double

Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity

<u>Code</u> <u>Description</u>

4XDR BRAKES, REAR (Meritor 16.5X7 Q-PLUS CAST) Air S-Cam Type, Cast Spider, Fabricated Shoe, Double

Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle

5710 STEERING COLUMN Tilting and Telescoping
5CAW STEERING WHEEL 4-Spoke; 18" Dia., Black
5PRR STEERING GEAR {TRW (Ross) TAS66} Power

6901 PROPSHAFT GUARD

6DGG DRIVELINE SYSTEM (Dana Spicer) 1710, for 4x2/6x2

7BMK EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Under Right Rail, for Single Long

Horizontal Tail Pipe

7SCP ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger

7WBL TAIL PIPE (1) Horizontal, Long, Exits Left Side Through Bumper

8000 ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: MISCELLANEOUS FEATURES Modular, Loom Protected, Grommets in all Applicable Body Openings, Assembled in Computer Assisted Fixture which Verifies Continuity and Correct Assembly Prior to Installation

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: TURN SIGNAL SWITCH Self-Cancelling with Lane Change Feature

: TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush

Mounted

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with

Turn Signal Lever

: WIRING, CHASSIS Color Coded and Continuously Numbered

8540 HORN, ELECTRIC (2) Trumpet Style

8GXN ALTERNATOR {Leece-Neville BLP4024N} Brushless, 12 Volt, 325 Amp Capacity, Pad Mount, with Remote

Sense

8MSG BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

8RMH BATTERY DISCONNECT SWITCH (Cole-Hersee 75920-06) 300 Amp, Disconnects Charging Circuits, Locks

with Padlock, Battery Box Mounted

8RRC RADIO AM/FM/USB Input/Auxiliary Input, Includes Wiring and Antenna, with Public Address System

8TTK BATTERY BOX Steel, with Sliding Tray, 25.25" Wide, for Standard Batteries, 1-3 Battery Capacity, Mounted

Left Side Behind Front Axle Perpendicular to Frame Rail

8TUT COLLISION MITIGATION SYSTEM Omit

8WRB HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On

8WTK STARTING MOTOR (Delco Remy 38MT Type 300) 12 Volt, Less Thermal Over-Crank Protection

8WWJ INDICATOR, LOW COOLANT LEVEL with Audible Alarm

8WXB HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position

8XAH CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

8XJE TURN SIGNALS, FRONT Dual Face, LED, Amber/Amber, Mounted on Top of Fender, Used with Standard

Flush Mounted Front Turn Signal, Side Marker Lamps, Parking Lights and Reflectors

3 Proposal: 8199-01

Description Code 8XKC HEADLIGHTS Halogen, with Daytime Running Lights, Automatic Twilight Controlled USB PORT One USB-A Port and One USB-C Port, Located in Instrument Panel 8XPN 9AAB **LOGOS EXTERIOR Model Badges** 9AAE LOGOS EXTERIOR, ENGINE Badges 9HCW **GRILLE Molded in Black** 9WAB HOOD TILT ASSIST {EASY TILT} Mechanical 9WBW FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes 10060 PAINT SCHEMATIC, PT-1 Single Color, Design 100 Includes : PAINT SCHEMATIC ID LETTERS "NB" 10788 PAINT TYPE Urethane, One or Two Colors, Other than Imron or International. 10AGB COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360 10WTU MULTI FUNCTIONAL BUS ID To be Used for Multi Functional School Activity Bus, Non Route Use Only, Letter of Compliance from End User is Required **10WUE** MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension 11001 **CLUTCH Omit Item (Clutch & Control)** 12703 ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection 12EYJ ENGINE, DIESEL {Cummins B6.7 260} EPA 2024, 260HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 260 Peak HP (Max), School Bus Only 12TJA FAN DRIVE {Warner Electric FC550} On/Off Type, Electronically Activated and Controlled : FAN Nylon **12UGN** THROTTLE, HAND CONTROL Electronic 12VCE AIR CLEANER Single Element, Fire Retardant Media 12VJR EMISSION, CALENDAR YEAR (Cummins B6.7) EPA, OBD and GHG Certified for Calendar Year 2024 **12VVN CRUISE CONTROL Electronic 12WCG** HOSE CLAMPS, RADIATOR HOSES (R.G. Ray Mini Flex Seal) Coil Spring/"T"-Bolt Constant Torque Type, for Radiator Hoses over 1" I.D. **12WPV** OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines **12WUL** BLOCK HEATER, ENGINE {Phillips} 120V/1000W, with "Y" Cord for Dealer Installed 120V/300W Oil Pan Heater

Includes

: BLOCK HEATER SOCKET Receptacle Type; Mounted in Center Through Front Bumper

12WVG EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified

Clean Idle" Decal on Hood

12WZE CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations

12XCC RADIATOR Aluminum, 2-Row, Down Flow, Front to Back System, 640 Sqln Louvered, with 383 Sqln Charge

Air Cooler, Includes In-Tank Oil Cooler

<u>Code</u>	Description Includes : RADIATOR HOSES Premium, Rubber
12XCS	CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty
13BDC	TRANSMISSION, AUTOMATIC {Allison 3000 PTS} 6th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, School Bus
13WET	TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission
13WLP	TRANSMISSION OIL Synthetic; 29 thru 42 Pints
13WUM	ALLISON SPARE INPUT/OUTPUT for Pupil Transportation Series (PTS), Package Number 148
13WVW	NEUTRAL AT STOP OMIT
13WYU	SHIFT CONTROL PARAMETERS (Allison) 3000 or 4000 Series Transmissions, Performance Programming
14AKZ	AXLE, REAR, SINGLE {Dana Spicer 23060SH} Single Reduction, 23,000-lb Capacity, R Wheel Ends . Gear Ratio: 5.57
14TEB	SUSPENSION, REAR, AIR, SINGLE {International IROS} 23,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers Mounted Outside the Rails
15LMR	FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor
15LRE	LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle
15SLL	FUEL TANK Top Draw, Steel, Rectangular, 100 US Gal (379L), Includes Protective Cage, Mounted Between Frame Rails and Behind Rear Axle
15WEP	DEF TANK 16.5 US Gal (62.5L) Capacity, Frame Mounted Outside Right Rail, Behind 0 Bow
16010	COWL Flat Back
16563	HEATER SHUT-OFF VALVES (2) Ball Valve Type
16BAM	AIR CONDITIONER with Integral Heater and Defroster
16GEG	GAUGE CLUSTER Premium Level; English with English Electronic Speedometer
	Includes : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure or Auxiliary Air Pressure (if Air Equipped) : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure, Primary and Secondary (if Air Equipped)
16HCH	SEATBELT WARNING LIGHT IND. Mounted in Dash, Will Flash when Park Brake is Disengaged and Driver Seatbelt Unfastened, Audible Alarm to Remind Driver to Fasten Seatbelt
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
16HLJ	GAUGE, DEF FLUID LEVEL
16VKB	CAB INTERIOR TRIM Classic, for Day Cab
16VVJ	WINDSHIELD Three Piece, Bonded, with Shaded Band
16XJP	INSTRUMENT PANEL Wing Panel
27DWT	WHEELS, FRONT (Accuride 43644) DISC; 22.5x8.25 Rims, Extra Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

Code **Description 28DWT** WHEELS, REAR (Accuride 43644) DUAL DISC: 22.5x8.25 Rims, Extra Polish Aluminum, 10-Stud, 285,75mm BC. Hub-Piloted, Flanged Nut, with Steel Hubs 47AJB **BODY CERTIFICATION TAG Mylar Label** 47AJC BODY TAG, METAL Capacity to Include the Total Number of Passengers 47AJZ BOWS, ROOF 12 ga., One Piece Construction Includes : BOWS, ROOF Positioned Floor Line to Floor Line, Threaded Through Roof Strainers and Drip Rail 47APR HEADLINER, BODY Conventional; 25'11"-35'08" Body Length, Perforated Full Length with Sound Insulation **Full Length** 47APW FASTENERS, HEADLINER Rivets 47ARJ REINFORCEMENT, BODY ROOF BOWS SPECIAL Construction Package, for Colorado, Utah, and Nebraska 47ARP LIGHT BARS Plastic 47ATB SKIRT, BODY Conventional, 20", 16ga., 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths Includes : SKIRT, BODY Extra Smooth Steel Supported by Floor Gussets 47AUR TIE DOWNS, BODY Grade 8 Bolts, Every Body Section : TIE DOWNS, BODY with Formed Tab that Fits into Floor Structure to Prevent Turning 47AVL BODY, BUS Conventional; 78" Headroom, 35'8" Body Length, +9 Section Front and Rear, 83 Passenger, 276 47AXT RUB RAILS, BODY (4) Conventional; Steel, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths, Includes Snow Rail Includes : RUB RAILS Full Length, Primer Coated (Both Sides), Attached to Body without Cuts or Splices 47AYB BODY, REAR Includes Emergency Door SIDE SHEET, BODY, EXTERIOR Conventional, 16ga., Smooth, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" 47AZE **Body Lengths** 47AZL FLOOR, BODY with Wheel Wells 47BAK BUMPER, REAR Painted, 12" High, 3/16" Thick 47BAR SUPPORTS, REAR BUMPER Bolted to Frame **47BBH** LINING, SIDE INTERIOR, LOWER Embossed Steel, Clear Coated 47BBZ SEALER Extra; Sidewall to Floor, In Wheel Pocket Area, and Rear Wall to Floor 47BDJ COMPARTMENT, DRIVER STORAGE Bin, Sized to Hold Three Ring Binder, Includes (1) USB-A Port and (1) **USB-C Port** 47BKY PAINT COLOR, BODY EXTERIOR 0001 Canyon Black 47BLE STEP, FRONT ENTRANCE DOOR 25 3/4" Depth; 14ga Steel, Formed Treads, Naviflex Finish 47DAE FASTENERS, REAR DOOR Lag Screws, Rear Door To Body 47DAJ COVER, REAR DOOR INSIDE HANDLE Partial Coverage 47DDE HANDLE, ASSIST, ENTRANCE DOOR Outside Entrance

6

<u>Code</u> <u>Description</u>

47DDH HOLD BACK, REAR DOOR Stationary, No Cables, with Plastic Cover

47DDU LATCH, REAR DOOR One Point Slide Bar, Cam Operated, with One Inch Stroke

47DRN SWITCH, LOCATION Left of Driver; Includes 2 Position Door Control

47EBM HOLD DOWN, BATTERY For Up To 3 Batteries

47EVK COMPARTMENT, LUGGAGE, LT MID 91" x 24" x 22"

includes

: HINGES Rubber

: LATCH, T-HANDLE, LOCKING Stainless Steel

47EWA COMPARTMENT, LUGGAGE, RT MID 114" X 24" X 22"
47EYL LOCK, ENTRANCE DOOR in External Release, with Key

47KBM STRIPING, PERIMETER, REAR (3M) Emergency Door, 1" White Fluorescent Diamond Grade
47KBN STRIPING, ROOF HATCH, FRONT (3M) Decal, Perimeter, 1" White Fluorescent Diamond Grade
47KBP STRIPING, ROOF HATCH, REAR (3M) Decal, Perimeter, 1" White Fluorescent Diamond Grade

47KDA STRIPING, SEATLINE (3M) 2" White Fluorescent Diamond Grade

47KDG STRIPING, REAR END (3M) White Fluorescent Diamond Grade, 1" Horizontal and 2" Vertical

47LAT NOISE REDUCTION, ROOF BOW Conventional: Insulation, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8"

Body Lengths

47LAU INSULATION, ROOF/SIDES/BULKHEAD 1.5"

47MAC UNDERCOAT, FLOOR/STEPWLL/SIDES for Engine Noise Reduction
47MBA UNDERCOAT, BODY Fire Resistant, Water Based, TT-C-730 Spec

<u>Includes</u>

: UNDERCOATING Performed Before and After Mounting on Chassis

47MTY WIRING DIAGRAM Schematic, Electrical

<u>Includes</u>

: ACCESS PANEL for Wiring Diagram Schematic Located on Inside of Electrical Panel Door, Below Driver

Window

47MVA LETTERS, HEADER Decal; "WATCH YOUR STEP", 1" Black, Above Windshield

47MVC LETTERS, STEPWELL Decal, "WATCH YOUR STEP", 2.5" Black, Behind Door on Step Riser

47MZA MONITOR, POST TRIP INSPECTION Omit

47MZB LETTERS, SCHOOL BUS FRONT/REAR Decal; OMIT "SCHOOL BUS"; with 8" Black Letters; on Front and

7

Rear Cap

47NBG LETTERS, DOOR, REAR Decals; "EMERGENCY DOOR", 2" Red Reflective Letters Inside and Outside

47NEK LETTERS, E/E WINDOW, LEFT (2) Decal Sets, "EMERGENCY EXIT", Red Inside and Outside

47NGW SEAL, RUB RAILS Top Edge, All Rails

47NHN LETTERS, E/E WINDOW, RIGHT (2) Decal Sets, "EMERGENCY EXIT", Red, Inside and Outside

47NJM PAINT FLASHER BACKGRD 0001 Canyon Black
47NJS PAINT COLOR, BUMPER Rear, 0001 Canyon Black

47NKL PAINT, RUB RAIL Flange to Flange

<u>Code</u> <u>Description</u>

47NKM PAINT COLOR, BODY INTERIOR 9384 Spring White
47NLR HANDLE, EXTERIOR, REAR Emergency Door; Black

47NMG OPERATING INSTRUCTIONS, REAR Decal, Inside Rear Emergency Door

47NTE LOGO, ROOF LINE Decal; Wing and Shield, First Body Section, Above Driver Window and Entrance Door

Over Driver Window and Entrance Door

47NTX PAINT COLOR, RUB RAILS To Match Body Exterior
47NTY PAINT HOOD AND FENDER To Match Body Exterior

47PBZ HANDLE, ASSIST Windshield Side Mounted, Left and Right, Body Color

47PCW DOOR, ENTRANCE, FRONT Electric, Outward Opening, with Single Pane Glass

47PDS STRIPING, E/E WINDOW, LEFT {3M} (02) Perimeter, 1" White Fluorescent Diamond Grade
47PDT STRIPING, E/E WINDOW, RIGHT {3M} (02) Perimeter, 1" White Fluorescent Diamond Grade

47PLX LETTERS, DEF, I.D. Decal; "DEF ONLY", 1" Black, on DEF Filler Door

47SBS SUB FLOOR, PLYWOOD Conventional; B-C Exterior Grade, Less Sealed Edges, 5/8", 5 Ply, for 31'2",31'11",

32'8",33'5", 34'2", 34'11", 35'8" Body Lengths

47SPK ALPHA/NUMERIC DECAL GUIDE Quantity 091-100

48ACN SEAT BELT, DRIVER, COLOR with Blaze Orange Seat Belt Webbing

48ANW WINDOW, DRIVER Storm

48APL WINDOW, STOPS 12" Opening, Only with 78" Headroom
48ARV WINDOW, SASH (21) 27" Sections, 9"x 23" Opening

48AUN WINDOW, PASSENGER, TINT Conventional; 28% Light, Laminated Glass, 78" Headroom, with 31'2", 31'11",

32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths

48BAH WINDOW, E/E, LEFT (2) Vertical Hinge

48BJA COLOR, WINDOW FRAME, PASS Passenger Window, Natural Aluminum Finish

48BKP WINDOW, E/E, RIGHT (2) Vertical Hinge

48DBN SHIELD, COURTESY, AFT ENTR DR Padded, 30", Mounted Under Stanchion

48DCA STANCHION, AFT ENTRANCE DOOR Padded, 30"

48DPL HAND RAIL, ENTRANCE DOOR, AFT 1" Dia, Stainless Steel

48HAG WINDOW, ENTRANCE DOOR Storm, Tempered, Clear, with Single Piece Glass

48PAV WHEEL POCKET COVER Plastic, ABS

48PAY AISLE POSITION Center, for balanced seating
48PEW FLOOR COVERING, COLOR Gray #766

48PKC HOSE CLAMPS, HEATER HOSE Constant Torque for Heater System

48PKR FAN, DEFOG LEFT CENTER 6.50" Diameter, Black, Mounted Left of Center Post, 2-Speed Switch in Panel

48PKS FAN, DEFOG RIGHT CENTER 6.50" Diameter, Black, Mounted Over Windshield, 15" Right of Centerline, 2-

Speed Switch in Panel

48PMC HEATER, PASS, LT MIDSHIP 1ST 50,000 BTU

Includes

<u>Code</u> <u>Description</u>

: AIR FILTER

48PMH HEATER, PASS, LT REAR 50,000 BTU

Includes

: AIR FILTER

48PMM HEATER, PASS, RT MIDSHIP 1ST 50,000 BTU

<u>Includes</u>

: AIR FILTER

48PNZ HEATER, WATER PUMP {2 MPU 12} Self Priming, Metal Housing

48PPS ROOF VENT, FRONT Static

48PUP FLOOR COVERING, TRIM Omit

48PVA UPHOLSTERY, DRIVER SEAT, STYLE Plain, with Cloth Insert
48PVN UPHOLSTERY, DRIVER SEAT, COLOR Drivers Seat, Gray

48PWD UPHOLSTERY, PASS SEATS, COLOR Gray, for Seats, Barriers and Head Bumpers

48PWR UPHOLSTERY, DRIVER SEAT, TYPE Prevaill, 42 oz.
48PXR UPHOLSTERY, BARRIER, TYPE (3-4) Prevaill, 42 oz.

48RAJ BARRIER, CRASH, AFT DRIVER 36", 1 Leg
48RBU BARRIER, CRASH, RT, 1ST Position, 36", 1 Leg

48REP PANEL, MODESTY, AFT OF DRIVER Mounted Under Barrier

48RLX CUSHION, SEAT 15" Depth

48RLZ COMPARTMENT, HEATER for Webasto Fuel Fired Heater, Mounted Left Side Behind Front Wheel Pocket

48RRA UPHOLSTERY, SEAT, STITCHING Single

48RYW SEAT, DRIVER (National 2000) Air Suspension, High Back with Integral Headrest, Isolated, with 2 Position

Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Mechanical Lumbar Support, Includes

Additional Back Padding

<u>Includes</u>

: SEAT BELT, DRIVER Adjustable D-Loop Seat Belt, Single Locking Retractor

48SBG UPHOLSTERY, PASS SEATS, TYPE Vinyl, 42 Ounce

48USV SEAT BACK, PASSENGER High Back

48UWW FLOOR COVERING, TYPE Koroseal, One Piece, Vinyl, All Body Lengths, Dark Gray

48UXS ARM REST, DRIVER Right

48UZN ROOF HATCH, FRONT (Specialty Hybrid Adv H1975-025-191-0F) Emergency Exit with Outside Release,

Alarm, English Decals

48UZT ROOF HATCH, REAR (Specialty Hybrid Adv H1975-025-191-0F) Emergency Exit with Outside Release,

Alarm, English Decals

48VVR STEP TREADS (Koroseal) Pebble White Nosing Only, with Non-Metal Backing, used with Formed Treaded

9

Steps

49001 BODY PLAN, APPROVED VARIATION Number 001

49AJJ CONNECTION, LIGHTS Wire Only, Front Cluster Lights to Ignition

CodeDescription49AJYSTOP ARM, FRONT Omit49AMTCIRCUIT, PROTECTION E

CIRCUIT, PROTECTION Breakers, Manual Reset in Lieu of Fuses

49AMV ALARM, BACKING (Ecco #850) 112 dB

49AMY SWITCH, REAR DOOR BUZZER for Emergency Door
49AWV SPEAKERS AND WIRING (8) Flush Mounted In Light Bar

49BCR LIGHT, EXTERIOR, CHECK Automatically Activates Lights for Pre Trip Inspection

49BGH LIGHTS, WARNING Omit All; To be Used for Multi Functional School Activity Bus, Non Route Use Only
49BGJ FLASHER SYSTEM Omit; To be Used for Multi Functional School Activity Bus or Commercial Models Only,

Non Route Use

49BTR WIRING MOD, DOME LIGHTS Mounted in Ceiling

49BYT LIGHTS, STOP (2) {Sound Off/OptiLuxx} and Tail; 7" Round LED, Red

49BYU LIGHTS, DOME, DRIVER (2) LED, Rectangular, Mounted Left and Right Sides in Ceiling, with Separate Switch

49BYZ LIGHTS, DIRECTIONAL, REAR (2) {Sound Off/OptiLuxx} LED, 7" Round Amber

49BZG LIGHTS, BACK UP (2) {Sound Off/OptiLuxx} LED, 7" Round Clear

49CKB LIGHT, INDIC, WARNING LIGHTS OMIT, To be Used for Multi Functional School Activity Bus, Non Route Use

Only

49CKT FUEL FILLER PIPE Low Profile Neck Cap and Vent Hosing, for Use with Right Side Fill for Between the Rail

Fuel Tanks, for Above the Floor Fuel Fill, for 25 GPM Fill Rate Only

49DDC LIGHTS, CLUSTER (Truck Lite 07045A & 07045R) LED; Amber Front and Red Rear

49DNB MIRROR, REAR VIEW, EXTERIOR (Rosco AccuStyle) Black, Motorized Head, Heated, Breakaway Bracket

49EGC MIRROR, INSIDE 6" x 30", Clear Safety Glass, Metal Back, Round Corners

49EGL MIRROR, CROSS VIEW, EXTERIOR (2) {Rosco Mini Hawk-Eye} Black

<u>Includes</u>

: MIRROR MOUNT Attached to Body with Metal Backing Plates

49ENK VISOR, INTERIOR, LEFT FRONT 6" x 30", Transparent, For Left Windshield

49EUB KIT, FIRST AID Metal; 24 Unit, Spec State

49EVL SWITCH, NOISE SUPPRESSION Actuator Legend States, "NOISE SUPP", for Separate Solenoid, with Red

Switch in Panel

49GAP KIT, BODY FLUID Montana

49GCH LOCATION, FIRST AID KIT Right Side Front Bulkhead with Screws

49GED SAFETY TRIANGLES Warning Reflectors, Mounted on Floor Between Driver Seat and Drivers Crash Barrier/

Stanchion/Partition

49GHN REFLECTORS, REAR (2) 3", Red, Adhesive Back

49GHR REFLECTORS, SIDE, REAR (2) 3", Red, Adhesive Back

49GHV REFLECTORS, SIDE, FRONT (2) 3", Amber; Adhesive Back, 1 Aft Drivers Window Left, 1 Aft Entrance Door

Right

49GHX REFLECTORS, SIDE, INTERMEDIATE (2) 3" Amber, 1 Each Side, Below The Third Rub Rail From the Top,

Adhesive Back

Code Description 49GKZ FUEL FILLER DOOR with Non-Locking Latch **49GUB** CUTTER, SEAT BELT (TIE TECH Safecut) for Cutting Seat Belts 49GUH CERTIFICATE HOLDER (1) 9.375" x 6"; with Transparent Cover INSPECTION PLATE Fuel Sending Unit 8" x 8" Steel 49GUM **49GUW** MOISTURE BARRIER, FLOOR Between Plywood and Steel; for AK Body 49GUY MUD FLAPS, REAR WHEELS (2) Anti-Spray, Anti-Sail 49JAC DEF FILLER DOOR with Non-Locking Latch HEATER, ENGINE COOLANT (Webasto Pro 90) Fuel Fired, 31,000 BTU, with Exhaust Exit Out Left Side **49JAP** 49JBU LIGHT, ENTRY DOOR (Sound Off/OptiLuxx) LED; 4" Oval; Light Mounted in Skirt Behind Entrance Door, Wired To Step Light **49JBW** LIGHT, STEP (Sound Off/OptiLuxx) 4" Round LED, White, Wired to Clearance Lights, Operated by Entrance Door **49JED** LIGHTS, MARKER, FRONT & REAR LED, Flush Mount, Amber Front and Red Rear **49JEK** LIGHTS, DOME LED, Rectangular Recessed Type, Two Full Rows, for 34'02", 34'11", 35'08" Body Lengths 49JEY LOCATION, BODY FLUID KIT on Bulkhead **49JGE** CUTTER, SEAT BELT, LOCATION Mounted on Panel Left of Driver FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle **49JGJ** 49JGN FIRE EXTINGUISHER. FRONT LOC Located Behind Driver Seat 49MSZ EXTRA WIRING Power Connection in Electrical Panel; Four Positions Fused at 20 Amps Each; (2) Battery and (2) Accessory **49MTB** TIMER, FUEL FIRED HEATER Digital, 7 Day, Programmable, for Webasto Fuel Fired Heater with SmarTemp Control, Mounted Right of Driver **49NGG** LIGHTS, TAIL, LICENSE PLATE (2) {Sound Off/OptiLuxx} 4" Round LED, Red, Includes Stop & Light Window, **Includes Mounting Gasket** 49PSY LIGHTS, DIRECTIONAL, SIDE (Sound Off/OptiLuxx) (2) Slim-Line LED Armored, Amber, (1) Each Side First Section Aft Entrance Door **49SAA** SWITCH, INSTRUMENT PANEL LIGHTS: Rheostat **49UBE** STATE OF OPERATION Montana 49ZNN LIGHTS, MARKER, SIDE, INTERMED LED, Amber, Flush Mount, Intermediate, Centered, Required for Units 30 Foot or Longer 7382135439 (2) TIRE, FRONT 11R22.5 Load Range H HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position 7382135444 (4) TIRE, REAR 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive

Services Section:

BODY PLAN, NON-SPECIAL NEEDS HARLO-2199

40126 WARRANTY Standard for CE, RE, BE School Bus Models, Effective with Vehicles Built March 1, 2017 or Later,

SUSPENSION, REAR, SINGLE TOPS is requiring susp, but I have air on proposal-TOPS error

CTS-3304H

OBD004

OBD008

December 04, 2023

<u>Code</u> <u>Description</u>

40RAK SERVICES, TOWING (Navistar) Service Call to 36-Month/Unlimited Mileage to the Nearest IC Bus Dealer for

Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage

& ESC Supplied thru Navistar; \$550 (USA) Maximum Benefit per Incident

40YGE SRV CONTRACT, EXT VEH COVERAGE (Navistar) To 36-Month/50,000 Miles (80,000 km), Covers 100%

Parts and Labor; Includes Body; Excludes Extending Warranty for Engine, Transmission, Perforation or

Corrosion of Cab/Cowl Structure and Paint

49GVN WARRANTY 5-Year, Limited

12 Proposal: 8199-01

Financial Summary 2025 CE SCHOOL BUS (PB110)

(US DOLLAR)

	(00 202211)	
<u>Description</u>		<u>Price</u>
Factory List Prices:		
Product Items	\$278,073.00	
Service Items	\$1,369.00	
Total Factory List Price Including Options:		\$279,442.00
C-Freedman Family Seats w/Level 4	\$16,800.00	
cloth, Gem Red uphoistery		
TA-A/C Roof mounted; 120k w/front/	\$15,300.00	
rear flush mounted evaps		
(TA55F55BR120 FB)		
C-USB ports for each seat (mtd on	\$2,050.00	
shoulder rail)		
C-Pretoria Open OPR's (no doors)	\$6,457.00	
Total Preparation And Delivery:		\$40,607.00
Freight Charge	\$4,500.00	
Total Freight:		\$4,500.00
Total Factory List Price Including Freight:		\$324,549.00
Less Customer Allowance:		(\$134,916.41)
Total Vehicle Price:		\$189,632.59
Total Sale Price:		\$189,632.59
Total Per Vehicle Sales Price:		\$189,632.59
Net Sales Price:		\$189,632.59

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an IC Corporation vehicle.

Hot Springs quote CE46 MFSAB w/Freedman Family seats.

Approved by Seller:	Accepted by Purchaser:
Official Title and Date	Firm or Business Name
Authorized Signature	Authorized Signature and Date
This proposal is not binding upon the seller without Seller's Authorized Signature	
	Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

13